

PATENT APPLICATION

042390.P5112

12. (Newly added) The method of claim 11, wherein the location of the first pseudo-noise code within the first codebook corresponds to the value of the first information signal for the first user

13. (Newly added) The method of claim 11 further comprising:
spreading a second information signal for the first user with a second pseudo-noise code contained within the first codebook.

14. (Newly added) The method of claim 13 wherein the location of the second pseudo-noise code within the first codebook corresponds to the value of the second information signal for the first user.

15. (Newly added) The method of claim 11 further comprising:
assigning a second codebook to a second user;
spreading a first information signal for the second user with a first pseudo-noise code contained within the second codebook.

16. (Newly added) The method of claim 15 further comprising:
spreading a second information signal for the second user with a second pseudo-noise code contained within the second codebook.

17. (Newly added) The method of claim 16 wherein the location of the second pseudo-noise code within the second codebook corresponds to the value of the second information signal for the second user.

18. (Newly added) The method of claim 11 further comprising:
despreading the first information signal for the first user with the first pseudo-noise code within the first codebook.

19. (Newly added) The method of claim 18 wherein the location of the first pseudo-noise code within the first codebook corresponds to the value of the first information signal.

PATENT APPLICATION

042390.P5112

20. (Newly added) The method of claim 11 wherein the partitioning the table of the orthogonal pseudo-noise codes further comprises:
partitioning the table into codebooks such that there are 2^n entries,
where n is a whole number.